

## *ICE CUBE BLACK SERIES*

**SUBWOOFER**



## ICE CUBE BLACK SERIES



Active Sub

Ice Cube 108 A Black Series



Ice Cube 108 P Black Series

SUBWOOFER



## ICE CUBE BLACK SERIES

### Features

- Subwoofer with solid steel basket, anti-resonance high gloss lacquering, 2" 4-layer voice-coil with additional ventilation, 30oz high power magnet with protection ring
- White LED illumination
- Loudspeaker fixed with metrical screws
- MDF enclosure
- Anti skid carpet with neoprene inlay and **HD**\* logo print



### Ice Cube 108 A Black Series:

- Active bandpass subwoofer with huge plexiglas window in cube design
- Digital amplifier
- Active amplifier module with high/low level input, full feature XO and auto turn-on function



### Ice Cube 108 P Black Series:

- Bandpass subwoofer enclosure with huge plexiglas window in cube design
- High quality screw terminal including LED remote function



\* HD = High Definition

**SUBWOOFER**

## **ICE CUBE 108 A BLACK SERIES**

Principle	1 x 8" powered bandpass subwoofer unit	
Max. power output (sine burst 2:8, 1 kHz) at 14.4V	400 watts	
RMS power output (DIN 45 324) at 14.4V	150 watts	
Frequency Response	28 – 150 Hz	
Supply voltage	12 V	
Input sensitivity	low level	100 mV Stereo/200 mV Mono
	high level	2.5 V
Input impedance	low level	10 kOhms
	high level	25 kOhms
Fuse size	25 A	
Dimensions (WxHxD/D)	370 x 280 x 275/315 mm	
Weight	11 kg	



**ACTIVE SUBWOOFER**

## **ICE CUBE 108 P BLACK SERIES**

**PASSIVE SUBWOOFER**

Description / DIN-Ø	Bandpass subwoofer with 8" driver
Power Handling RMS/max	250 / 800 watts
Impedance	4 ohms
Frequency Response	23 – 500 Hz
Sound Pressure Level	89 dB
Driver	Polypropylen cone
Dimensions (WxHxD/D)	370 x 280 x 275/315 mm
Weight	9 kg

